



Performance. Power.  
Productivity.™

# DFPXP


## 20ga. 1/2" Crown Clinching Stapler

The DFPXP is a compact, lightweight, yet powerful clinch stapler. It is designed with high quality components for dependable all-day use in industrial applications.



### Specifications

|                         |                        |
|-------------------------|------------------------|
| Item #                  | 8H0001N                |
| UPC                     | 741474095535           |
| Mode of Operation       | Sequential Actuation   |
| Reg. Operating Pressure | 65-100 psi (4 - 7 bar) |
| Air Inlet               | 1/4" NPT               |
| Tool Weight             | 4.9 lbs (2.24 kg)      |
| Height                  | 12.9" (327 mm)         |
| Length                  | 14.9" (380 mm)         |
| Width                   | 3.0" (75 mm)           |
| Throat Depth            | 6.9" (175 mm)          |
| Fastener Capacity       | 230                    |



### Fastener Specifications

|           |                           |
|-----------|---------------------------|
| Gauge     | 20                        |
| Crown     | 1/2" (12.7 mm)            |
| Length    | 5/16" - 5/8" (8mm - 16mm) |
| Finish    | Galv.                     |
| Collation | Glued Strip               |

### Applications

Corrugated box fabrication, light assembly and packaging, shoe making.

### Features and Benefits

- High capacity magazine holds 230 staples – less reloading means maximum production
- Tool-free adjustable anvil opening
- Rubber comfort grip reduces vibration, slipping, and fatigue
- Bottom-load magazine for quick reloading
- 6.9" throat allows for extended reach into cartons
- 5 year limited warranty

### SENCO® 20 Ga. 1/2" Crown Fine Wire

| Length | Item Code | Carton Count | Point  | Finish    | Coating |
|--------|-----------|--------------|--------|-----------|---------|
| 3/16"  | F05BAAP   | 24.M         | Chisel | Galv      | Plain   |
| 3/8"   | F06BAA    | 10.M         | Chisel | Galv      | Plain   |
| 3/8"   | F06BAAP   | 24.M         | Chisel | Galv      | Plain   |
| 1/2"   | F08BAAN   | 10.M         | Chisel | Galv      | Plain   |
| 1/2"   | F08BAAP   | 10.M         | Chisel | Galv      | Plain   |
| 3/8"   | F06BGA    | 10.M         | Chisel | Stainless | Plain   |
| 1/2"   | F08BGA    | 10.M         | Chisel | Stainless | Plain   |

**Contact Actuation Trigger** (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

**Sequential Actuation Trigger** (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

For additional information on how Senco will save you time, reduce costs, and increase quality, call us at 1-800-543-4596 to find your nearest Authorized Senco Dealer or Distributor or visit our web site at: [www.senco.com](http://www.senco.com)